

jolie atelier

Sanitas Wallcoverings are manufactured by:
RJF International Corporation
3875 Embassy Parkway
Fairlawn, Ohio 44333

Sanitas Wallcoverings
FACT SHEET
Pattern Name: Anouschka

QUIK SPEC	U.S. UNITS:	METRIC UNITS:
<i>Total Weight:</i>	21 oz. PLY	651 g. PLM
	14 oz. PSY	475 g. PSM
<i>Roll Width:</i>	55/56 in.	139/142 cm.
<i>Gauge (average):</i>	0.022 in.	0.56 mm.
<i>Fabric:</i>	Non-woven	
<i>Tensile (minimum):</i>	50 x 50 lb _f	222 x 222 N
<i>Tear (minimum):</i>	25 x 25	---
<i>WA Spec:</i>	WA-W-101, Type II	---
<i>Fire Testing:</i>	NFPA 101 [®] Life Safety Code [®] NFPA 255 (UL723, CAN S102M) Tunnel Test ¹ - Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
<i>Repeat: Horizontal</i>	17.75 in.	45.0 cm
<i>Vertical</i>	22.25 in.	56.5 cm
<i>Nominal Pattern Width:</i>	54"	
<i>Hanging Instructions:</i>	Non-Reverse – Straight Match	
1. When tested on GRC board with A-848-B adhesive 2. When tested on 5/8" type X gypsum board with A-848-B adhesive		

COLORLINE

8 Colorways

Pattern Description: Soft diffused twig or field stalk, understated and useable for all market segments.

JM18-45 Smokey Topaz	JM18-33 Amber	JM18-86 Whispers
JM18-61 Purple Haze	JM18-17 Toffee	JM18-82 Mirage
JM18-30 Golden Mist	JM18-29 Soft Cashmere	<i>Note: Cannot be split to 27."</i>

Notes:

- "Pattern Width" is the trim width on the specification and represents the width of the wallcovering that will be received by the customer.
- "Gauge" is the product thickness measured after the first pattern colorway is produced.
- "Tensile" and "Tear" results are the minimums required by specification WA-101 Wallcovering Association Quality Standard for Polymer Coated Fabric Wallcovering.
- "Nominal Pattern Width" is the expected width yield from one drop on the wall.