

Cavollo has the look of a finely woven fabric texture that is reminiscent of a crinkled Italian silk found in today's market and has a rich translucent quality which makes it appear almost transparent.

	US UNITS	METRIC UNITS
Total Weight	21.0 oz PLY 14.0 oz PSY	651 g PLM 475 g PSM
Roll Width	53/54 in.	135/137 cm
Gauge	23 Mils	0.58 mm
Fabric	Osnaburg	
Tensile (Minimum)	50 x 55 lb _f	222 x 245 N
Tear (Minimum)	25 x 25	
Federal Spec	CCC-W-408A, Type II	
CFFA Spec	CFFA-W-101-D, Type II	
Fire Testing	NFPA 101 [®] Life Safety Code [®] NFPA255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover UL Labeled and Listed	
Repeat	Vertical Horizontal Match Information	N/A N/A Random Match, Reverse Hang
1 When applied to GRC Board with A-848-B adhesive		2 When applied to 5/8" Type-X gypsum board with A-848-B adhesive

Available in 5 Colorways

- ML20-06
- ML20-19
- ML20-27
- ML20-48
- ML20-57