

jolie atelier

Sanitas Wallcoverings are manufactured by:
RJF International Corporation
3875 Embassy Parkway
Fairlawn, Ohio 44333

Sanitas Wallcoverings
FACT SHEET
Pattern Name: Cayenne

QUIK SPEC	U.S. UNITS:	METRIC UNITS:
Total Weight:	21 oz. PLY	651 g. PLM
	14 oz. PSY	475 g. PSM
Roll Width:	52/54 in.	132/137 cm.
Gauge (average):	0.020 in.	0.51 mm.
Fabric:	Osnaburg	
Tensile (minimum):	50 x 50 lb _f	222 x 222 N
Tear (minimum):	25 x 25	---
WA Spec:	WA-W-101, Type II	---
Fire Testing:	NFPA 101 [®] Life Safety Code [®] NFPA 255 (UL723, CAN S102M) Tunnel Test ¹ - Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
Repeat: Horizontal	N/A	
Nominal Pattern Width:	51"	
Hanging Instructions:	Reverse – Random	
1. When tested on GRC board with A-848-B adhesive 2. When tested on 5/8" type X gypsum board with A-848-B adhesive		

COLORLINE

7 Colorways

Pattern Description: Vertical and horizontal prints that provide balanced texture; highly versatile.

JM09-26 Rainwashed	JM09-12 Cream Silk	JM09-30 Misty Blush*
JM09-67 Iron Ore	JM09-38 Desert Tan*	JM09-84 Mirage*
JM09-73 Sea Foam	<i>Can be split to 27."</i>	

Notes:

- "Pattern Width" is the trim width on the specification and represents the width of the wallcovering that will be received by the customer.
- "Gauge" is the product thickness measured after the first pattern colorway is produced.
- "Tensile" and "Tear" results are the minimums required by specification WA-101 Wallcovering Association Quality Standard for Polymer Coated Fabric Wallcovering.
- "Nominal Pattern Width" is the expected width yield from one drop on the wall.

*These decorative metallic effect wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners (ex. Lestoil[®]) have the potential to damage the surface of the wallcovering as does excessive scrubbing.