



**Koroseal Wallcoverings are manufactured by:**

**RJF International Corporation  
3875 Embassy Parkway  
Fairlawn, Ohio 44333**

**Koroseal Wallcoverings  
FACT SHEET**

**Pattern Name: Cornice**

**QUIK SPEC**

**U.S. UNITS:**

**METRIC UNITS:**

<i>Total Weight:</i>	24 oz. PLY	744 g. PLM
	16 oz. PSY	543 g. PSM
<i>Roll Width:</i>	53/55 in.	134/139 cm.
<i>Gauge (average):</i>	0.027 in.	0.69 mm.
<i>Fabric:</i>	Non-Woven	---
<i>Tensile (minimum):</i>	50 x 50 lb <sub>f</sub>	222 x 222 N
<i>Tear (minimum):</i>	25 x 25	---
<i>WA Spec:</i>	WA-W-101, Type II	---
<i>Fire Testing:</i>	NFPA 101 <sup>®</sup> Life Safety Code <sup>®</sup> NFPA 255 (UL723, CAN S102M) Tunnel Test <sup>1</sup> - Class A Rating NFPA 286 Corner Burn Test <sup>2</sup> Meets requirements for Flame Spread, Smoke Developed and Flashover	
<i>Repeat: Horizontal</i>	3.375 in.	8.53 cm.
<i>Vertical</i>	.75 in.	1.90 cm.
<i>Nominal Pattern Width:</i>	53 in.	134 cm.
<i>Hanging Instructions:</i>	Reverse - Straight Match	
<i>Special Instructions:</i>	1. When tested on GRC board with A-848-B adhesive 2. When tested on 5/8" type X gypsum board with A-848-B adhesive	

\*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the wallcoverings as does excessive scrubbing.

**COLORLINE**

**15 Colorways**

*Pattern Description:* Unique, beautiful texture inspired by tin ceilings and architectural detailing.

9C24-91 Flashing*	9C24-68 Limelight	9C24-46 Crowning Touch
9C21-06 Carving	9C24-87 Showdown*	9C24-57 Tinker
9C24-11 A Spire	9C24-49 Cantina*	9C24-63 Shady Lady*
9C24-37 Tin Pan Alley*	9C24-70 Piano Player *	9C24-99 Brown's Saloon
9C24-42 Sarsparilla*	9C24-94 Boardwalk	9C24-40 Pass the Buck*

**Notes:**

- "Pattern Width" is the trim width on the specification and represents the width of the wallcovering that will be received by the customer.
- "Gauge" is the product thickness measured after the first pattern colorway is produced.
- "Tensile" and "Tear" results are the minimums required by specification WA-101 Wallcovering Association Quality Standard for Polymer Coated Fabric Wallcovering..
- "Nominal Pattern Width" is the expected width yield from one drop on the wall.