Vicrtex®

3875 Embassy Parkway
Fairlawn, OH 44333

(800) 828-4556 www.koroseal.com

Currents©

FACT SHEET

Currents© is a textural interpretation of the Oceans' currents. Continuous and directed movement of hot or cold water rivers within the ocean. Our design is a soft, flowing current in the vertical direction bringing peace and harmony to your interiors.

		US UNITS	METRIC UNITS
Total Weight		21.0 oz PLY 14.0 oz PSY	651 g PLM 475 g PSM
Roll Width		52/54 in.	132/137 cm
Gauge		23 Mils	0.56 mm
Fabric		Osnaburg	
Tensile (Minimum)		50 x 50 lb_f	222 x 222 N
Tear (Minimum)		25 x 25	
WA Spec		WA-W-101, Type II	
Fire Testing		NFPA 101® Life Safety Code® NFPA255 (UL723, CAN S102M) Tunnel Test[1] Class A Rating NFPA 286 Corner Burn Test[2] Meets requirements for Flame Spread, Smoke Developed and Flashover	
Repeat	Vertical	N/A	
	Horizontal	N/A	
	Nominal Pattern Width	51 in.	129 cm
	Match Information	Random Match, Reverse Hang	

1 When applied to GRC Board with A-848-B adhesive

2 When applied to 5/8" Type-X gypsum board with A-848-B adhesive

Available in 15 Colorways

*CZ21-47 Copper Bronze
CZ21-37 Dune
CZ21-30 Eddy
CZ21-11 Froth
*CZ21-95 Glacier
CZ21-06 Icicle
CZ21-69 Lava
*CZ21-54 Liquid Gold
*CZ21-52 Orange Glow
*CZ21-98 Pewter
CZ21-34 Reflection
CZ21-78 Rivulet
*CZ21-81 Sea Grass
CZ21-24 Trickle
*CZ21-73 Waterfall

*** These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.**

Vicrtex® is a registered trademark of RJF International Corporation Currents© is a copyright of RJF International Corporation
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association
©2008 RJF International Corporation
22-47-CZ21/09/2008