

A rich, luxurious leather look characterized by cuts or slices on the surface of the material, artistically placed to create a plaid design. This unique take on leather is sure to be a winner and is appropriate for hospitality and corporate applications.

	US UNITS	METRIC UNITS
Total Weight	21.0 oz PLY 14.0 oz PSY	651 g PLM 475 g PSM
Roll Width	53/55 in.	135/140cm
Gauge	18 Mils	0.46 mm
Fabric	Non-Woven	
Tensile (Minimum)	50 x 50 lb _f	222 x 222 N
Tear (Minimum)	25 x 25	
WA Spec	WA-W-101, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
Repeat	Vertical	29.5 in. 75 cm
	Horizontal	51.25 in. 130 cm
	Nominal Pattern Width	51.25 in. 130 cm
	Match Information	Straight Match, Non-Reverse Hang
1 When applied to GRC Board with A-848-B adhesive		2 When applied to 5/8" Type-X gypsum board with A-848-B adhesive

Available in 20 Colorways

- | | | |
|-------------|--------------|---------------|
| 51030 Pearl | 51038 Stone | *51046 Nature |
| 51031 Pearl | *51039 Dawn | *51047 Nature |
| 51032 Pearl | 51040 Dawn | 51048 Nature |
| 51033 Sand | 51041 Lava | |
| 51034 Sand1 | *51042 Zinc | |
| 51035 Sand | *51043 Zinc | |
| 51036 Stone | 51044 Zinc | |
| 51037 Stone | *51045 Ocean | |

*** These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.**