

Lasso's playful surface is composed of carefree, meandering lines looping back over and over again. The pattern pays respect to both positive and negative space, even breaking up the background to enhance the negative area.

	US UNITS	METRIC UNITS
Total Weight	21.0 oz PLY 14.0 oz PSY	651 g PLM 475 g PSM
Roll Width	53 in.	135 cm
Gauge	21 Mils	0.53 mm
Fabric	Osnaburg	
Tensile (Minimum)	50 x 50 lb _f	222 x 222 N
Tear (Minimum)	25 x 25	
WA Spec	WA-W-101, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA 255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
Repeat	Vertical	7.5 in. 19 cm
	Horizontal	13 in. 33 cm
	Nominal Pattern Width	52 in. 132 cm
	Match Information	Straight Match, Non-Reverse
	1 When applied to GRC Board with A-848-B adhesive	2 When applied to 5/8" Type-X gypsum board with A-848-B adhesive

Available in 14 Colorways

X821-84 Aloe	X821-15 Rawhide
X821-25 Antler	X821-75 Riverstone
X821-81 Cactus	X821-07 Rope
X821-53 Chile Pepper	X821-39 Saddle
X821-32 Gold Rush	X821-96 Spurs
X821-36 Mesa	X821-21 Tumbleweed
X821-17 Prairie	X821-88 Well Water