

jolie atelier

Sanitas Wallcoverings are manufactured by:
RJF International Corporation
3875 Embassy Parkway
Fairlawn, Ohio 44333

Sanitas Wallcoverings
FACT SHEET
Pattern Name: Matisse

QUIK SPEC	U.S. UNITS:	METRIC UNITS:
<i>Total Weight:</i>	21 oz. PLY	651 g. PLM
	14 oz. PSY	475 g. PSM
<i>Roll Width:</i>	52/54 in.	137/139 cm.
<i>Gauge (average):</i>	0.021 in.	0.53 mm.
<i>Fabric:</i>	Non-woven	
<i>Tensile (minimum):</i>	50 x 50 lb _f	222 x 222 N
<i>Tear (minimum):</i>	25 x 25	---
<i>WA Spec:</i>	WA-W-101, Type II	---
<i>Fire Testing:</i>	NFPA 101 [®] Life Safety Code [®] NFPA 255 (UL723, CAN S102M) Tunnel Test ¹ - Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
<i>Repeat: Horizontal</i>	4.50 in.	11.4 cm
<i>Vertical</i>	2.25 in.	5.73 cm
<i>Nominal Pattern Width:</i>	51"	
<i>Hanging Instructions:</i>	Non-reverse – Straight Match	
1. When tested on GRC board with A-848-B adhesive 2. When tested on 5/8" type X gypsum board with A-848-B adhesive		

COLORLINE

8 Colorways

Pattern Description: Light on dark, fluid vine with tiny leaves – like Matisse might paint.

JM16-68 Firethorn	JM16-27 Anjou Pear	JM16-09 Desert Floor
JM16-14 Ivoire	JM16-31 Maplewood	JM16-15 Seed Pearl
JM16-83 Dusty Miller	JM16-62 Emberglow	

Notes:

- “Pattern Width” is the trim width on the specification and represents the width of the wallcovering that will be received by the customer.
- “Gauge” is the product thickness measured after the first pattern colorway is produced.
- “Tensile” and “Tear” results are the minimums required by specification WA-101 Wallcovering Association Quality Standard for Polymer Coated Fabric Wallcovering.
- “Nominal Pattern Width” is the expected width yield from one drop on the wall.