

jolie atelier

Sanitas Wallcoverings are manufactured by:
RJF International Corporation
3875 Embassy Parkway
Fairlawn, Ohio 44333

Sanitas Wallcoverings
FACT SHEET
Pattern Name: Pacha Stripe

QUIK SPEC	U.S. UNITS:	METRIC UNITS:
<i>Total Weight:</i>	21 oz. PLY	651 g. PLM
	14 oz. PSY	475 g. PSM
<i>Roll Width:</i>	55/56 in.	139/142 cm.
<i>Gauge (average):</i>	0.020 in.	0.51 mm.
<i>Fabric:</i>	Non-woven	
<i>Tensile (minimum):</i>	50 x 50 lb _f	222 x 222 N
<i>Tear (minimum):</i>	25 x 25	---
<i>WA Spec:</i>	CCC-W-408A, Type II	---
<i>Fire Testing:</i>	NFPA 101 [®] Life Safety Code [®] NFPA 255 (UL723, CAN S102M) Tunnel Test ¹ - Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
<i>Repeat: Horizontal</i>	4.50 in.	11.4 cm
<i>Vertical</i>	0.63 in.	1.60 cm
<i>Nominal Pattern Width:</i>	51"	
<i>Hanging Instructions:</i>	Reverse – Match Stripes	
1. When tested on GRC board with A-848-B adhesive 2. When tested on 5/8" type X gypsum board with A-848-B adhesive		

COLORLINE

2 Colorways

Pattern Description: A delicate woven fabric chain with subtle striping.

JM05-57 Burnt Almond	JM05-83 Sawgrass	<i>Note: Can not be cut to 27."</i>
----------------------	------------------	-------------------------------------

Notes:

- "Pattern Width" is the trim width on the specification and represents the width of the wallcovering that will be received by the customer.
- "Gauge" is the product thickness measured after the first pattern colorway is produced.
- "Tensile" and "Tear" results are the minimums required by specification WA-101 Wallcovering Association Quality Standard for Polymer Coated Fabric Wallcovering.
- "Nominal Pattern Width" is the expected width yield from one drop on the wall.