

Streamline® is a textural patchwork of pounded metal squares. This illusion is enhanced with the use of translucent metallic inks giving the product a brushed metal appearance.

	US UNITS	METRIC UNITS
Total Weight	21.0 oz PLY 14.0 oz PSY	651 g PLM 474.4 g PSM
Roll Width	52/54 in.	132/137 cm
Gauge	19 Mils	.48 mm
Fabric	Osnaburg	
Tensile (Minimum)	50 x 50 lb _f	222 x 222 N
Tear (Minimum)	25 x 25	
WA Spec	WA-W-101, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
Repeat	Vertical	1 7/8" – 2 in. 4.76 – 5.08 cm
	Horizontal	1 7/8" – 2 in. 4.76 – 5.08 cm
	Match Information	Straight Match, Reverse Hang
	1 When applied to GRC Board with A-848-B adhesive	2 When applied to 5/8" Type-X gypsum board with A-848-B adhesive

Available in 17 Colorways

- | | |
|----------------------|---------------------|
| *S921-51 Breakers | *S921-62 Royal Sea |
| *S921-80 Cascade | *S921-25 Sandcastle |
| S921-88 Dew Drop | S921-19 Sand Dollar |
| *S921-33 Gold Rush | S921-04 Sea Shell |
| S921-82 Kelp | S921-23 Starfish |
| *S921-79 Over Flow | *S921-58 Sunset |
| S921-30 Oyster Pearl | S921-94 Trickle |
| *S921-37 Pure Gold | *S921-90 Whirlpool |
| S921-47 Reflections | |

* These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners (ex. Lestoil®) have the potential to damage the surface of the material along with excessive scrubbing.