Vicrtex®

3875 Embassy Parkway
Fairlawn, OH 44333

(800) 828-4556 www.koroseal.com

Vintage©

FACT SHEET

This weathered paint design was inspired by the backdrops used in many fashion photos. Vintage's aged appearance is enhanced by the use of an inkwiped, crackle texture and provides instant ambiance for any interior space.

		US UNITS	METRIC UNITS
Total Weight		21.0 oz PLY 14.0 oz PSY	651 g PLM 475 g PSM
Roll Width		52/54 in.	132/137 cm
Gauge		20 Mils	0.51 mm
Fabric		Osnaburg	
Tensile (Minimum)		50 x 50 lb_f	222 x 222 N
Tear (Minimum)		25 x 25	
WA Spec		WA-W-101, Type II	
Fire Testing		NFPA 101® Life Safety Code® NFPA255 (UL723, CAN S102M) Tunnel Test[1] Class A Rating NFPA 286 Corner Burn Test[2] Meets requirements for Flame Spread, Smoke Developed and Flashover	
Repeat	Vertical	N/A	
	Horizontal	N/A	
	Nominal Pattern Width	51 in.	130 cm
	Match Information	Random Match, Reverse Hang	

1 When applied to GRC Board with A-848-B adhesive

2 When applied to 5/8" Type-X gypsum board with A-848-B adhesive

Available in 18 Colorways

VT21-52 Abstract	VT21-36 Impressionist	VT21-40 Realism
VT21-95 Baroque	VT21-43 Medieval	VT21-88 Renaissance
VT21-19 Classical	VT21-47 Nouveau	VT21-83 Rococo
VT21-15 Contemporary	VT21-31 Op Art	VT21-07 Romantic
VT21-86 Deco	VT21-22 Precisionism	VT21-38 Surreal
VT21-49 Expressionist	VT21-44 Primitive	VT21-29 Symbolism

Vicrtex® is a registered trademark of RJF International Corporation Vintage© is a copyright of RJF International Corporation
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association
©2008 RJF International Corporation