

Vicrtex Wallcoverings  
A division of RJF International Corp.  
3875 Embassy Parkway  
Fairlawn, OH 44333

**VICRTEX WALLCOVERING**  
FACT SHEET  
**VIZCAYA**

<b>QUIK SPECS</b>	<b>U.S. UNITS</b>	<b>METRIC UNITS</b>
Total Weight:	25.0 oz. / linear yard 16.7 oz / square yard	775.1 g. PLM 565.2 g. PSM
Fabric Weight:	3.0 oz. / linear yard	93.0 g. PLM
Vinyl Weight:	22.0 oz. / linear yard	682.1 g. PLM
Roll Width:	52 / 54 inches	132/137 cm.
Thickness:	0.031 average inches	0.79 average mm.
Fabric:	Osnaburg	
Tensile (W x F):	50 x 50	Tear (W x F): 25 x 25
E-84 Tunnel Test:	Flame Spread: 15	Smoke Developed: 20
<b>HANGING INSTRUCTIONS:</b>		
Special Instructions:	<b>Reverse Strips</b> <b>Non-Match</b>	

**Follow hanging instructions provided in roll shipment.**

General installation instructions and warranty information can be found by consulting the SPECIFICATIONS insert found in the front of every Vicrtex AIA catalog or "Installation Instructions" or "Architect's Specifications for Vinyl Wallcovering" technical / data sheets available from your distributor or RJF International Corp. in Fairlawn, OH.

Do follow roll number sequence - starting with largest roll number. Use panels / strips IN EXACT ORDER as they are cut from roll. Always fill in over doors and windows as you come to them with panels cut in consecutive order from roll.

**After three panels have been installed and evaluated, it may be necessary to additionally trim one or both selvage edges to obtain conformity across seams. If there is any question of color or pattern matching, promptly consult your local Vicrtex representative.**

---

VIZCAYA is available in 29 colors.  
Custom colors and a minimum weight of 24 oz. can be ordered.  
Tedlar application is not recommended.