

Watermark Parquet® expands upon Watermark's visual image by including a piece of driftwood in the scene. This was translated by using a hand-carved wood grain texture applied in quarter-turned squares to the surface of the product.

	US UNITS	METRIC UNITS
Total Weight	21.0 oz PLY 14.0 oz PSY	651 g PLM 475 g PSM
Roll Width	52/54 in.	132/137 cm
Gauge	20 Mills	.54 mm
Fabric	Non-Woven	
Tensile (Minimum)	50 x 50 lb _f	222 x 222 N
Tear (Minimum)	25 x 25	
WA Spec	WA-W-101, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
Repeat	Vertical	1 7/8- 2 in. 4.76- 5.08 cm
	Horizontal	1 7/8- 2 in. 4.76- 5.08 cm
	Match Information	Half Drop Match, Reverse Hang
	1 When applied to GRC Board with A-848-B adhesive	2 When applied to 5/8" Type-X gypsum board with A-848-B adhesive

Available in 18 Colorways

W621-08 Biscay Bay	W621-59 Magma
W621-65 Bridgeport	W621-95 Night Tide
W621-29 Candlelight	W621-61 Otter Creek
W621-57 Clayridge	W621-10 Sea Crest
W621-31 Daydream	W621-82 Seaweed
W621-15 Feather Down	W621-36 Stone Cove
W621-03 Glass Glow	W621-44 Stonington
W621-20 Golden Gate	W621-22 Streamline
W621-34 Honey Glaze	W621-76 Tidal Basin