

## Manufactured by: Koroseal Interior Products, LLC

3875 Embassy Parkway Fairlawn, Ohio 44333



A deep watery, metallic effect with a handcrafted troweled emboss.

	U.S. UNITS	METRIC UNITS
Total Weight	21 oz PLY	651 g. PLM
	14 oz PSY	475 g. PSM
Roll Width	52/54 in.	132/137 cm
Gauge	0.027 in.	0.68 mm
Fabric	Osnaburg	
Tensil (minimum)	50 x 55 lb <sub>f</sub>	222 x 245 N
Tear (minimum)	25 x 25 lb <sub>f</sub>	
Federal Spec	CCC-W-408A, Type II	
WA Spec	WA-101, Type II	
Fire Testing	NFPA 101 <sup>®</sup> , Life Safety Code®	
	NFPA 255 (UL 723, CAN S102M) Tunnel Test <sup>1</sup>	
	Class A Rating	
	NFPA 286 Corner Burn Test <sup>2</sup>	
	Meets requirements for Flame Spread, Smoke Developed and Flashover	
Repeat		
Horizontal	N/A	
Vertical	N/A	
Match Information	Random Match, Reverse Hang	
Nom. Pattern Width	51 in.	130 cm

<sup>&</sup>lt;sup>1</sup> When applied to GRC board with A-848-B adhesive

## Available in 16 Colorways

9B21-02 Crystal Lattice	9B21-52 Knighthood*
9B21-22 Golden Pearl	9B21-55 Shields Up!*
9B21-35 Aladdin's Lamp	9B21-58 Oxidized*
9B21-38 Anodize	9B21-59 Gyrados*
9B21-41 Pendant	9B21-65 Merlin
9B21-44 Copperclad*	9B21-79 Grail*
9B21-47 Brass Ring	9B21-80 Hammered Steel
9B21-49 Hot Tin Roof*	9B21-90 Excalibur

<sup>\*</sup>These decorative metallic effect wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners (ex. Lestoil®) have the potential to damage the surface of the wallcovering as does excessive scrubbing.

 $<sup>^2</sup>$  When applied to 5/8" type-X gypsum board with A-848-B adhesive