



| | | | | |
|--|--|-----------------------|---|--|
| 16 Colorways: | LSV1-01 Snowy Owl LSV1-02 Mountain Hare LSV1-03 Silver Moth* LSV1-04 Walking Stick LSV1-05 Leopard* LSV1-06 Orchid Mantis LSV1-07 Sloth* LSV1-08 Seadragon* | | LSV1-09 Camouflage* LSV1-10 Katydid* LSV1-11 Mamba LSV1-12 Butterfly Wing* LSV1-13 Tiger* LSV1-14 Tree Lizard* LSV1-15 Scarlet Macaw* LSV1-16 Chameleon* | |
| | *These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent, and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing. | | | |
| Designer | Koroseal | | | |
| Total Weight | 25.0 oz. ply (775 g. plm.) | Vertical Repeat | N/A | |
| Roll Width | 52-54 in. (132-137 cm.) | Horizontal Repeat | N/A | |
| Backing | Woven (Osnaburg) | Nominal Pattern Width | 52 in. | |
| Tensile (Minimum) | 50 x 55 lb _f (222 x 245 N) | Match Information | Non-Reverse Hang, Random Match | |
| Tear (Minimum) | 25 x 25 lb _f (111 x 111 N) | WA Spec. | WA-101, Type II | |
| Federal Spec. | CCC-W-408D, Type II | ASTM F-793 | Category V, Type II | |
| Fire Testing | NFPA 101® Life Safety Code® | | | |
| | NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test ¹ - Class A Rating | | | |
| | NFPA 286 Corner Burn Test ² - Meets requirements for Flame Spread, Smoke Developed, and Flashover | | | |
| | 1 When applied to GRC board 2 When applied to 5/8" Type-X-Gypsum board | | | |
| CE Certification | EU classification in accordance with EN 15102:2007 + A1:2011 | | | |
| Indoor Air Quality | California 01350 – Meets emission requirements for schools and offices | | | |
| For additional technical information please visit koroseal.com | | | | |

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.
 ©2024 Koroseal Interior Products, LLC.

68-47-LSV1 | 08/2019