



11 Colorways:	7 7

7322-07 Blonde 7322-08 Dunes* 7322-09 Envy* 7322-10 Ebony 7322-41 Purlesque* 7322-51 Flaxen* 7322-59 Espresso* 7322-65 Bordeaux* 7322-70 Royalty* 7322-79 Magical* 7322-94 Mineralism*

*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent, and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

Designer	Koroseal		
Total Weight	20.0 oz. ply (618 g. plm.) 13.3 oz. psy (451 g. psm.)	Vertical Repeat	24 in.
Roll Width	53-55 in. (134-140 cm.)	Horizontal Repeat	10.375 in.
Backing	Non-Woven	Nominal Pattern Width	52 in.
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information	Reverse Hang, Straight Match
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II
Fire Testing	NFPA 101 [®] Life Safety Code [®] NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test ¹ - Class A Rating NFPA 286 Corner Burn Test ² - Meets requirements for Flame Spread, Smoke Developed, and Flashover 1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive		
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011		
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices		

For additional technical information please visit koroseal.com

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com

Koroseal[®] is a registered trademark of Koroseal Interior Products, LLC. NFPA 101[®] and Life Safety Code[®] are registered trademarks of National Fire Prevention Association. ©2024 Koroseal Interior Products, LLC.